



CROSS SECTIONAL VIEW

### DIMENSIONS

SKU	D (mm)	d (mm)	D1 (mm)	L1 (mm)	L2 (mm)	Threaded Section		d2 (mm)	D2 (mm)	H (mm)	H1 (mm)	W (mm)	t (mm)	WEIGHT (Kg)	PCS/CTN
						d1 (inch)	No. of Screw Threads (per 25.4mm)								
AWFT013	24	18.40±0.20	28	17	14	RP ½"	14	26	34	38	29	4	3.0	0.038	400
AWFT01513	29	22.40±0.20	28	17	14	RP ½"	14	26	34	43	32	4	3.5	0.045	260
AWFT02013	33	26.45±0.20	29	17	14	RP ½"	14	32	42	47	34	4	3.0	0.060	200
AWFT020	33	26.45±0.20	35	19	16	RP ¾"	14	32	42	51	36	4	3.5	0.06	160
AWFT025	40	32.55±0.25	46	21	18	RP 1"	11	40	52	59	42	5	4.0	0.125	80

### Notes:

1. The threaded section of JIS B 0203 (pipe taper thread) is the parallel female thread.
2. The tolerance for L2 is  $\pm 1$ mm. The tolerance for H is +5 and -1mm. The tolerance for H1 is +5 and -2mm.
3. The tolerance for D depends on the common dimensions of socket.