

## **VU/AW REDUCE TEE**

COMPLY WITH JIS K 6743





















CROSS SECTIONAL VIEW





**CROSS SECTIONAL VIEW** 

DIMENCIONO											
DIMENSION	15										
SKU	D	d	D1	d1	t	Н	H1	Z	Z1	WEIGHT	1.00,
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(Kg)	CTN
AWRT01513	29	22.40±0.20	24	18.40±0.20	3.5	41	38	11	12	0.045	320
AWRT02013	33	26.45±0.20	24	18.40±0.20	3.5	46	40	11	14	0.059	200
AWRT02015	33	26.45±0.20	29	22.40±0.20	3.5	48	45	13	15	0.059	200
AWRT02513	40	32.55±0.25	24	18.40±0.20	4.0	51	43	11	17	0.078	140
AWRT02515	40	32.55±0.25	29	22.40±0.20	4.0	53	48	13	18	0.086	120
AWRT02520	40	32.55±0.25	33	26.45±0.20	4.0	55	53	15	18	0.091	100
AWRT03513	46	38.60±0.25	24	18.40±0.20	4.0	55	46	11	20	0.099	100
AWRT03515	46	$38.60 \pm 0.25$	29	22.40±0.20	4.0	57	51	13	21	0.103	80
AWRT03520	46	38.60±0.25	33	26.45±0.20	4.0	59	56	15	21	0.111	80
AWRT03525	46	38.60±0.25	40	32.55±0.25	4.0	62	61	18	21	0.132	72
AWRT04213	57	48.70±0.30	24	18.40±0.20	4.5	66	52	11	26	0.152	60
AWRT04215	57	48.70±0.30	29	22.40±0.20	4.5	68	57	13	27	0.173	56
AWRT04220	57	48.70±0.30	33	26.45±0.20	4.5	70	62	15	27	0.182	50
AWRT04225	57	48.70±0.30	40	32.55±0.25	4.5	73	67	18	27	0.208	46
AWRT04235	57	48.70±0.30	46	38.60±0.25	4.5	76	71	21	27	0.200	46
AWRT05013	70	60.80±0.30	24	18.40±0.20	5.0	74	58	11	32	0.227	40
AWRT05015	70	60.80±0.30	29	22.40±0.20	5.0	76	63	13	33	0.258	34
AWRT05020	70	60.80±0.30	33	26.45±0.20	5.0	78	68	15	33	0.280	34
AWRT05025	70	60.80±0.30	40	32.55±0.25	5.0	81	73	18	33	0.283	30
AWRT05035	70	60.80±0.30	46	38.60±0.25	5.0	84	77	21	33	0.297	26
AWRT05042	70	60.80±0.30	57	48.70±0.30	5.0	90	88	27	33	0.345	22
AWRT06550	87	76.60±0.30	70	60.80±0.30	6.6	101	104	40	41	0.616	18
AWRT08025	102	89.60±0.30	40	32.55±0.25	8.0	93	88	29	48	0.670	18
AWRT08042	102	89.60±0.30	57	48.70±0.30	8.0	100	102	36	47	0.816	14
AWRT08050	102	89.60±0.30	70	60.80±0.30	8.0	105	110	41	47	0.907	12
AWRT08065	102	89.60±0.30	87	76.60±0.30	8.0	113	117	49	56	1.012	10
AWRT10050	130	114.70±0.30	70	60.80±0.30	10.0	125	122	41	59	1.486	6
AWRT10080	130	114.70±0.30	102	89.60±0.30	10.0	140	132	56	68	1.818	5
AWRT125100	157	140.85±0.35	130	114.70±0.30	11.0	173	167	69	83	3.317	3
AWRT15080	186	166.00±0.40	102	89.60±0.30	13.0	195	158	63	94	4.246	2
AWRT150100	186	166.00±0.40	130	114.70±0.30	13.0	208	182	76	98	4.954	2
AWRT150125	186	166.00±0.40	157	140.85±0.35	13.0	217	201	85	97	5.125	2
AWRT200100	243	217.40±0.70	134	114.70±0.30	13.0	218	200	73	116	6.500	1
AWRT200150	243	217.40±0.70	189	166.00±0.40	13.0	245	257	100	125	8.400	1
*AWRT250150	300	268.60±0.70	189	166.00±0.40	14.5	355	524	180	392	8.400	1
AWRT250200	300	268.60±0.70	243	217.40±0.70	14.5	335	335	160	190	16.100	1
*AWRT300150	356	319.80±0.80	189	166.00±0.40	16.0	375	561	190	429	30.800	1
*AWRT300200	356	319.80±0.80	243	217.40±0.70	16.0	410	599	225	454	37.700	1
AWRT300250	356	319.80±0.80	300	268.60±0.70	16.0	375	392	190	217	25.500	1

**Notes:** 1. The tolerance for H is +5 and -1mm.

- 2. The tolerance for D, D1 and t depends on the common dimensions of socket.
- 3. R is more than 10mm.