PRESS CONNECTION TOOLS

RP306 PRESS TOOL

SKU:PFMR15050N306



SPECIFICATIONS:

- Crimp pipe diameter 15-50mm
- 270° Rotate the jaws.
- Output pressure: 32kN
- Weight Without Battery: 2.6kg.
- Single crimping time: 7 seconds
- Standard Battery: 18V 2.5Ah Lithium Battery
- Standard Battery Charger: 230V
- Compatible with standard series crimping jaws of RIDGID and other manufactures.
- suitable for copper pipes, steel pipes, stainless steel pipes, PEX and composite pipes.

Components List of RP306 Set

No	SKU	Description	Quantity	Weight (kg)/pc
1	PFMRA-	RP306 Pressing Tool	1	2.6
2	PFMRA-67583	15mm Pressing Jaw	1	1.80
3	PFMRA-67588	20mm Pressing Jaw	1	1.86
4	PFMRA-67593	25mm Pressing Jaw	1	1.96
5	PFMRA-67598	35mm Pressing Jaw	1	2.07
6	PFMRA-77723	42mm Swivel Ring	1	1.37
7	PFMRA-77728	54mm Swivel Ring	1	1.15
8	PFMRA-70168	Swivel Ring Actuator	1	1.85
9	PFMRA-56513	Batteries	2	0.47
10	PFMRA-64388	Battery Charger	1	0.86
11	-	Sling	1	-
12	RID29993	Reamer (1/2" to 2")	1	0.56
13	RID31803	Tubing Cutter	1	0.68

RIDGID

WARNING

ONLY USE TESTED AND APPROVED JAWS AND /OR ATTACHMENTS FOR RIDGID PRESS TOOL.

PRESSING JAW PATENT



APPROVED PRESSING JAWS IN SINGAPORE



RP 318 JAW RP 380 JAW RP 218 JAW

THESE PRESSING JAWS ARE ACCEPTED FOR MASS PRODUCTION AND DISTRIBUTION TO THE MARKET.

SAFETY REMINDER

USE OF INCORRECT PRESS TOOLS AND/OR ATTACHMENTS CAN CAUSE SYSTEM LEAKS, DAMAGE THE PRESS TOOLS AND ATTACHMENTS OR CAUSE SEVERE PERSONAL INJURY.

