

ESLON ADHESIVE NO.70P



APPLICATIONS

Adhesive for vinyl chloride pipe
High-viscosity type for summertime and medium-diameter pipes.

STANDARD SPECIFICATIONS

STOCK CODE	SCS500
BRAND	SEKISUI
STANDARDS	JAPAN WATER WORKS ASSOCIATION STANDARD B JWWA S101
COM	TAIWAN(ROC)
MAX VISCOSITY	HIGH-VISCOSITY QUICK DRYING 2500MPA.S
SELF LIFE	2 YEARS
MAX PIPE SIZE	DN 200 industrial grade
PACKAGE	500G / TIN WITH BRUSH 10TINS / BOX 4 BOXES / CARTON 448 CARTONS / 20 FT FCL(17,920TINS)
MSDS UN NUMBER	1133 (Adhesive, containing inflammable liquid)
MSDS UN CLASSIFICATION	Class 3 (inflammable liquid)

Nominal Diameter		Spread (coating amount of solvent cement) per joint (inside of socket + outside of spigot end), gram
In	(mm)	
2	50	5.0
2 1/2	65	6.5
3	75	8.5
4	100	13.5
5	125	20.0
6	150	30.0
8	200	54.0
10	250	84.0
12	300	120.0
14	350	163.0